

AMENDMENTS**In the Claims**

The following is a marked-up version of the claims with the language that is underlined ("___") being added and the language that contains strikethrough ("—") being deleted:

1. — 40. (Canceled)

41. (New) A method for coupling a universal serial bus network adapter supporting both a remote network drive interface specification and a non-network drive interface specification, the method performed by a network adapter, the method, comprising:

providing a plurality of universal serial bus configurations to a universal serial bus network;

receiving a first request from a host, the host coupled to a device;

returning a remote network drive interface specification configuration from the network adapter;

receiving a second request from the host, in response to receiving an indication of multiple support configurations;

returning a non-remote network drive interface specification configuration, where the host is configured to parse the received configuration to determine the configuration supported by the device and where the host is configured to select a configuration that matches a client driver.

42. (New) The method of claim 41, wherein the client driver is a remote network drive interface specification (RNDIS).

43. (New) The method of claim 41, wherein the client driver is a communications data class Ethernet (CDC-Ethernet).

44. (New) The method of claim 41, wherein the network adapter determines whether any sub-system that corresponds to any configuration is currently active.

45. (New) The method of claim 41, wherein the network adapter determines whether the active configuration matches the currently active sub-system, the method further comprising issuing a command to disable the sub-system when there is no match, and issuing a command to activate a new sub-system corresponding to the new configuration selected by the host.

46. (New) A method, at a host, for coupling universal serial bus devices network adapter supporting both remote network drive interface specification and non-network drive interface specification, comprising the steps of:

- detecting a network device, the network device operating on a first configuration;
- issuing a universal serial bus reset to the network device;
- sending the reset to the network device for resetting the state of the network device;
- issuing a command enabling the network device to communicate on the universal serial bus according to a second configuration;
- issuing a command enabling a retrieval of device descriptors from the network device;
- returning a device descriptor indicating a function of the network device; and
- issuing configuration commands, whereby, the network device is configured to return a list of descriptors.

47. (New) The method of claim 46, wherein the resetting of the state of the network device involves disabling one of a remote network drive interface specification (RNDIS) and a communications data class Ethernet (CDC-Ethernet).

48. (New) The method of claim 46, wherein the list of descriptors for the configuration commands is for a remote network drive interface specification (RNDIS) or a communications data class Ethernet (CDC-Ethernet).

49. (New) The method of claim 46, wherein the host discards the configuration for a remote network drive interface specification (RNDIS).

50. (New) The method of claim 46, wherein the host accepts the configuration for the communications data class Ethernet (CDC-Ethernet).

51. (New) The method of claim 46, wherein the host issues a configuration to the device to use the communications data class Ethernet (CDC-Ethernet) configuration.

52. (New) An apparatus for coupling universal serial bus devices network adapter supporting both remote network drive interface specification and non-network drive interface specification, comprising the steps of:

a universal serial bus network configured to receive a plurality of universal serial bus configurations;

a receiving component configured to receive a first request from a network adapter;

a network adapter for returning a remote network drive interface specification configuration, the network adapter receiving a second request from a host, when there is an indication of multiple support configurations;

a parsing component for parsing all the received configuration to determine the configuration supported by the device; and

wherein the host selects the configuration that matches a client driver.

53. (New) The apparatus of claim 52, wherein the client driver is a remote network drive interface specification (RNDIS).

54. (New) The apparatus of claim 52, wherein the client driver is a communications data class Ethernet (CDC-Ethernet).

55. (New) The apparatus of claim 52, wherein the network adapter determines whether any sub-system corresponds to any configuration is active.

56. (New) The apparatus of claim 52, wherein the network adapter determines whether the active configuration matches the currently active sub-system, issues a command to disable the sub-system when there is no match, and issues a command to activate a new sub-system corresponding to the new configuration selected by the host.

57. (New) An apparatus for attaching a universal serial bus network adapter supporting both remote network drive interface specification and non-network drive interface specification, comprising:

a detecting component configured to detect a network device communicating via a first configuration, and for issuing a universal serial bus reset to a network device by a host, and resetting a state of the network device, and for receiving a network device at a universal serial bus port;

a first issuing component configured to issue a command enabling the network device to communicate on the universal serial bus via a second configuration;

a second issuing component configured to issue a command for retrieving device descriptors from the network device; and

a third issuing component configured to issue configuration commands, whereby, the network device returns a list of descriptors.

58. (New) The apparatus of claim 57, wherein the resetting of the state of the network device involves disabling one of a remote network drive interface specification (RNDIS) and a communications data class Ethernet (CDC-Ethernet).

59. (New) The apparatus of claim 57, wherein the list of descriptors for the configuration commands are for a remote network drive interface specification (RNDIS) or a communications device class Ethernet (CDC-Ethernet).

60. (New) The apparatus of claim 57, wherein the host discards the configuration for a remote network drive interface specification (RNDIS).

61. (New) The apparatus of claim 57, wherein host accepts the configuration for the communications data class Ethernet (CDC-Ethernet).

62. (New) The apparatus of claim 57, wherein the host issues a configuration to the device to use for the communications data class Ethernet (CDC-Ethernet).

63. (New) A system for attaching a universal serial bus network adapter supporting both remote network drive interface specification and non-network drive interface specification, comprising:

- a providing component configured to provide two universal serial bus configurations to a universal serial bus network;

- a first receiving component configured to receive a first request from a host;

- a first returning component configured to return a remote network drive interface specification configuration from the network adapter;

- a second receiving component configured to receive a second request from a host, when there is an indication of multiple support configurations;

- a second returning component configured to return a non-remote network drive interface specification configuration from the network adapter;

- a parsing component configured to parse all the received configuration to determine the configuration supported by the device; and

- a selecting component configured to select a configuration that matches a client driver.

64. (New) The system of claim 63, wherein the client driver is a remote network drive interface specification (RNDIS).

65. (New) The system of claim 63, wherein the client driver is a communications data class Ethernet (CDC-Ethernet).

66. (New) The system of claim 63, wherein the network adapter determines whether any sub-system that corresponds to any configuration is active.

67. (New) The system of claim 63, wherein the network adapter determines whether the active configuration matches the currently active sub-system, the system further comprising a first issuing component configured to issue a command to disable the sub-system when there is no match, and a second issuing component configured to issue a command to activate a new sub-system corresponding to the new configuration selected by the host.

68. (New) A system for attaching a universal serial bus network adapter supporting both remote network drive interface specification and non-network drive interface specification, comprising:

- a universal serial bus port configured to receive a network device according to a first configuration;

- a detecting component configured to detect the network device coupled to the universal serial bus port;

- a first issuing component configured to issue a universal serial bus reset to the network device to reset the state of the network device;

- a second issuing component configured to issue a command to enable the network device to communicate on the universal serial bus according to a second configuration;

- a third issuing component configured to issue a command to retrieve device descriptors from the network device;

- a receiving component configured to receive a device descriptor listing indicating its function from the network device; and

a fourth issuing component configured to issue configuration commands, whereby, the network device returns a list of descriptors.

69. (New) The system of claim 68, wherein resetting of the state of the network device comprises disabling one of a remote network drive interface specification (RNDIS) and a communications data class Ethernet (CDC-Ethernet).

70. (New) The system of claim 68, wherein the device descriptor listing for the configuration commands is for a remote network drive interface specification (RNDIS) or a communications data class Ethernet (CDC-Ethernet).

71. (New) The system of claim 68, further comprising a discarding component configured to discard the configuration for a remote network drive interface specification (RNDIS).

72. (New) The system of claim 68, further comprising an accepting component configured to accept the configuration for the communications data class Ethernet (CDC-Ethernet).

73. (New) The system of claim 68, further comprising a fourth issuing component configured to issue a configuration to the device to use the communications data class Ethernet (CDC-Ethernet) configuration.

74. (New) A computer-readable media containing a computer-executable program for attaching a universal serial bus network adapter supporting both remote network drive interface specification and non-network drive interface specification, the program comprising:

- one or more instructions for issuing a universal serial bus reset to the network device by the host, the network device operating to a first configuration;

- one or more instructions for resetting the state of the network device;

- one or more instructions for enabling the network device to communicate on the universal serial bus according to a second configuration;

- one or more instructions for issuing by the host a command enabling to retrieve device descriptors from the network device;

- one or more instructions for returning by the network device a computer code device descriptor indicating its function; and

- one or more instructions for issuing by the host configuration commands, whereby, the network device returns a list of descriptors.

75. (New) The computer-readable media of claim 74, wherein the one or more instructions for resetting of the state of the network device further comprises one or more instructions for disabling one of a remote network drive interface specification (RNDIS) and a communications data class Ethernet (CDC-Ethernet).

76. (New) The computer-readable media of claim 74, further comprising one or more instructions for discarding the configuration for a remote network drive interface specification (RNDIS).

77. (New) The computer-readable media of claim 74, further comprising one or more instructions for accepting the configuration for the communications data class Ethernet (CDC-Ethernet).

78. (New) The computer-readable media of claim 74, further comprising one or more instructions for issuing a configuration code instructing the device to use the communications data class Ethernet (CDC-Ethernet) configuration.